

**LIGHTSPAN+ PRO T8 BATTEN 4FT POWER & CCT ADJUSTABLE -
22/27/34/40W 3000/4000/6500K 2970-5800LM 145LM/W 120 BEAM LINKABLE
NON-DIMM INTEGRAL**

ILBTC160

**Details**

Quick Order Code:	259950
Barcode:	5055788291978
Category:	Luminaires
Range Name:	Lightspan+ PRO
Type:	Single / Twin
Product Type:	Battens
Product Body Finish:	Matt white
Market Segment:	Indoor commercial, Industrial, residential
Features:	Power & CCT Swtichable
Warranty (Years):	5
CE RoHS:	Yes

Physical Data

Product Length (mm):	1170
Product Depth (mm):	71
Product Width (mm):	60
Product Weight (g):	1700
Optic:	Polycarbonate diffuser
Material:	Steel, Polycarbonate
Construction:	Folded Mild Steel and Polycarbonate diffuser
Bulb or Luminaire Shape:	Linear
Luminaire Fixing:	Ceiling mounted
Placement / Application:	Indoor, General Lighting

Electrical Data

Power Consumption (W) :	22/27/34/40
Power Factor:	0.9
Voltage Range (v):	200-240
Input Voltage (V):	200-240
Dimming:	Non-Dimmable
Driver Included:	Yes

Electric Current:	AC
EN:	EN-60598
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	22W: 2970/3300/2970 27W: 3510/3920/3510 34W: 4420/4930/4420 40W: 5200/5800/5200
Correlated Colour Temperature (CCT) (K):	3000/4000/6300
Colour Temperature:	3000/4000/6300 - Warm White/Cool White/Cool Daylight
Colour Temperature Name:	Warm White/Cool White/Cool Daylight
Beam Angle:	120
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Size (mm):	2835
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	50000
Switching Cycles:	25000

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
New Energy Rating:	D
EU Luminaire:	L
Hg 0% (Mercury Free):	Yes
IK Rating (Impact Protection):	IK08
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40

Packaging

Package Weight (g):	1800
Package Length (mm):	1175
Package Width (mm):	68
Package Depth (mm):	79