

**TOUGH SHELL COMPACT CIRCULAR PIR BULKHEAD 215MM DIA 10W  
1100LM 3000/4000/6000K SWITCHABLE CCT IP65 IK10 110LM/W INCLUDING  
WHITE AND BLACK BEZELS INTEGRAL LED**

ILBHP001

**Details**

<b>Quick Order Code:</b>	939814
<b>Barcode:</b>	5055788292319
<b>Category:</b>	Luminaires
<b>Range Name:</b>	Tough Shell Compact
<b>Product Type:</b>	Bulkheads-Ceiling-Wall Lights
<b>Product Body Finish:</b>	Matt white and black
<b>Market Segment:</b>	Indoor and Outdoor Commercial, Industrial, Residential
<b>Features:</b>	Adjustable PIR Sensor, CCT Switchable
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	215
<b>Product Depth (mm):</b>	65
<b>Product Width (mm):</b>	215
<b>Product Weight (g):</b>	380
<b>Optic:</b>	Polycarbonate
<b>Material:</b>	Polycarbonate
<b>Overall diameter (mm):</b>	215
<b>Construction:</b>	Polycarbonate casing and diffuser
<b>Bulb or Luminaire Shape:</b>	Round
<b>Luminaire Fixing:</b>	Wall Mounted
<b>Placement / Application:</b>	Indoor, Outdoor, General Lighting
<b>Wiring / Mounting Options:</b>	Rear cable entry

**Electrical Data**

<b>Power (W):</b>	15
<b>Power Consumption (W) :</b>	10
<b>Power Factor:</b>	0.9
<b>Voltage Range (v):</b>	220-240
<b>Dimming:</b>	Non-Dimmable

<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>Emergency Lumens (lm):</b>	No
<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	1100
<b>Luminous efficacy (lm/W):</b>	110
<b>Correlated Colour Temperature (CCT) (K):</b>	4000
<b>Colour Temperature Name:</b>	Cool White
<b>Beam Angle:</b>	120
<b>Colour Rendering Index (CRI):</b>	80
<b>Frequency Range (Hz):</b>	50/60
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	50000
<b>Sensor / Override:</b>	Yes with sensor
<b>Switching Cycles:</b>	25000

## Environment

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IK Rating (Impact Protection):</b>	IK10
<b>IP Rating (Ingress Protection):</b>	IP65
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45

## Packaging

<b>Package Weight (g):</b>	500
<b>Package Length (mm):</b>	230
<b>Package Width (mm):</b>	230
<b>Package Depth (mm):</b>	85
<b>Qty per euro pallet:</b>	160